



TECHNICKÁ DATA PROXIMA

| | | | | | | | | |
|----------------------------------|----------|-----------|---|------|------|------|-------------|---------|
| Pracovní šířka | A | [mm] | 1700 | 2200 | 2700 | 3200 | dále po 500 | až 6000 |
| Šířka dráhy | B | [mm] | 2100 | 2600 | 3100 | 3600 | dále po 500 | až 6600 |
| Celková šířka stroje | C | [mm] | 2800 | 3300 | 3800 | 4300 | dále po 500 | až 7300 |
| Pracovní šířka s jedním suportem | D | [mm] | 1700 | 2200 | 2700 | 3200 | dále po 500 | až 6200 |
| Pracovní délka | | [m] | dle přání (3.5, 4.5, 6, 8.5, 11, 12, 16, 18.5, 21, . .) | | | | | |
| Max. počet suportů | | [ks] | 6 | | | | | |
| Pracovní rychlost | | [mm/min.] | 10 - 15 000 | | | | | |
| Výška materiálového stolu | | [mm] | 600 - 700 | | | | | |

TLOUŠTKY ŘEZANÉHO MATERIÁLU

| | | [mm] | | | | | | | | | |
|-------------------|--------------------------|------|---|---|---|----|----|----|----|-----|-----|
| | | 1 | 2 | 4 | 8 | 15 | 30 | 60 | 80 | 125 | 250 |
| AUTOGEN | Acetylén | | | | | | | | | | |
| | Propan | | | | | | | | | | |
| | Zemní plyn | | | | | | | | | | |
| PLAZMA | Vanad 163 CNC | | | | | | | | | | |
| | Vanad 203 CNC | | | | | | | | | | |
| | Hypertherm Powermax 1000 | | | | | | | | | | |
| | Hypertherm Powermax 1250 | | | | | | | | | | |
| | Hypertherm MAX 100 | | | | | | | | | | |
| | Hypertherm MAX 100D | | | | | | | | | | |
| | Hypertherm MAX 200 | | | | | | | | | | |
| | Hypertherm HD 3070 | | | | | | | | | | |
| | Hypertherm HD 4070 | | | | | | | | | | |
| | Hypertherm HT 2000 | | | | | | | | | | |
| | Hypertherm HT 4400 | | | | | | | | | | |
| | Kjellberg HiFocus 100 | | | | | | | | | | |
| | Kjellberg PA-S 25 | | | | | | | | | | |
| | Kjellberg PA-S 45 | | | | | | | | | | |
| | Kjellberg FineFocus 450 | | | | | | | | | | |
| Kjellberg PA-S 75 | | | | | | | | | | | |

VANAD s.r.o., Obora 315, 582 82 Golčův Jeníkov

tel: 569 400 440 - 3, fax: 569 400 444

e-mail: vanad@vanad.cz

http:// www.vanad.cz